

TECHNICAL DATA

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers



Key features

- 6-digit backlight display reads the data clearly
- Signal detection reminder avoids invalid detection actions
- Maximum/minimum/average value and final readings
- Setting/Turning off the automatic power-off function
- Small size and easy to hold
- Easy switching of the contact and non-contact measurement modes
- Different speed measuring heads and rotational speeds adapt to different measurement occasions
- 1-year warranty

Product overview: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

The Fluke 931 tachometer is a handheld tachometer, which integrates the contact and non-contact speed measurement functions and can accurately measure the revolutions per minute (RPM) or surface speed and distance. Fluke 930 is equivalent to a Fluke 931 with minimum configuration. With only the non-contact measuring function provided, it's more affordable and offers consistent quality.

Applications:

· Heavy manufacturing environments, e.g. automotive, textile, pulp and paper, metalwork



- Water purification plants
- Machining and chemical manufacturing plants
- HVAC compressors for industrial systems


Specifications: Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

Rotation speed measurement	
Range	Optical (non-contact) measurement: 1 to 99999 revolutions/minute Contact measurement: 1 to 19999 revolutions/minute (Fluke 931 only)
Precision	±0.02%RD+1
Sensing distance	(optical) 500 mm

Specifications		
Battery type	(2) 1.5V LR6 (alkaline) AA battery	
Battery life	About 40 hours	
Operating temperature	0°C to 50°C	
Storage temperature	-20°C to 70°C	
Weight	250 g	
Dimensions	175 × 60 × 28 mm	
Warranty period	1 year	



Ordering information



Fluke 931

Fluke 931 Contact and Non-Contact Dual-Purpose Tachometers

- 0.1 m wheel
- Conical speed measuring head
- Inner cone speed measuring head
- Lengthening rod
- 10 reflective stripes



Fluke. Keeping your world up and running.®

Fluke Corporation

PO Box 9090, Everett, WA 98206 U.S.A.

Representative office of Fluke South East Asia Pte

Ltd

C/O Danaher Vietnam

Green Power Tower, 11th Floor Unit 2 35 Ton Duch Thang Street, District 1

Ho Chi Minh City Vietnam

Tel: +84-8-2220-5371 (ext 103) Email: info.asean@fluke.com www.fluke.com/vn-vi

©2024 Fluke Corporation. Specifications subject to

change without notice.

10/2024

Modification of this document is not permitted without written permission from Fluke Corporation.

For more information call: In the U.S.A. (800) 443-5853

In the U.S.A. (800) 443-585. In Europe/M-East/Africa +31 (0)40 267 5100 In Canada (905) 890-7600

From other countries +1 (425) 446-5500