#### | Technical Specifications

Specifications		
DC voltage (V)	6.000V/60.00V/600.0V	±(1%+3)
AC voltage (V)	6.000V/60.00V/600.0V	±(1%+4)
Resistance	600.0Ω/6.000kΩ/60.00kΩ/600.0kΩ	±(1%+3)
	6.000ΜΩ	±(1.5%+5)
	60.00ΜΩ	±(2.5%+5)
Capacitance	600.0nF/6.000uF/60.00uF/600.0uF	±(3.5%+8)
	6.000mF	±(5.0%+9)
	60.00mF	±(10.0%+9)
Frequency	99.99Hz/999.9Hz/9.999kHz /99.99kHz/999.9kHz	±(0.01%+5)
Features		
Display count	6000	
Duty cycle	0.1% to 99.9%	

	7	
Features		
Display count	6000	
Duty cycle	0.1% to 99.9%	
NCV/LIVE test	V	
True RMS	V	
Diode	V	
Continuity	V	
Resistance	V	
Auto range	V	
Screen	HTN LCD 36 x 15mm	
Auto power off	V	
Flash light	V	
Indicator	Dual color Dual color	
Battery	AAA x 1	
Category rating	CAT IV 300V, CAT III 600V	
Characteristics		
Power supply	AAA x 1	
Product dimension	182.5 x 38.0 x 38.5mm	
Product color	Gray + Red	
Accessories	User manual 1pcs, 1.5V AAA battery 1pcs	





# **UNI-TREND TECHNOLOGY**















## Safety and convenient







CAT III 600V CAT IV 300V



CAT II 600V

### Gold-plated special-tip test lead

With its gold-plated special-tip test lead, this product makes electronic measurements effortless and precise.



## Portable and lightweight design



This meter's portable and lightweight design offers operators convenience and ease of use, making it a versatile and indispensable tool for various tasks.

## Safety & reliable







This meter ensures safe and reliable measurements with CAT III 600V and CAT IV 300V certifications, providing accurate readings and minimizing electrical hazards.

## Power supply







