

The UT890C/D+ 6000-count true RMS digital multimeters are designed with large LCD display. The maximum measurable capacitance is 100mF, with fast response time of less than 12s. The NCV and continuity measurement have acousto-optic indications. UT890D+ has a LIVE function for distinguishing between live and neutral wires. In addition, it is equipped with the automatic fuse blown detection and high voltage protection.

Applications:

- Electrical switchboards; HVAC systems;
- Electrical circuit faults detection;
- Installation or maintenance of electronics/ factory equipment;
- Electronics component;
- development, circuit board design;
- Users who need to distinguish between neutral/ live wire frequently.



Live and nature wires identification



UT890D+

Specifications	Range	UT890C	UT890D+
DC voltage	600mV/6V/60V/600V/1000V	±(0.7%+3)	±(0.7%+3)
AC voltage	6V/60V/600V/750V	±(0.8%+3)	±(0.8%+3)
ACV Frequency	10Hz~10kHz	±(0.1%+5)	±(0.1%+5)
DC current	60μA/600μA/6mA/60mA/600mA/20A	±(0.8%+8)	±(0.8%+8)
AC current	60μA/600μA/6mA/60mA/600mA/20A	±(1%+12)	±(1%+12)
Resistance	600Ω/6kΩ/60kΩ/600kΩ/6MΩ/60MΩ	±(0.8%+3)	±(0.8%+3)
Capacitance	100mF	±(3%+10)	±(3%+10)
Frequency	9.999Hz~9.999MHz	±(0.1%+5)	±(0.1%+5)
Temperature	-40°C~1000°C/-40°F~1832°F	±(1%+3)	
Display count		6000	6000
Live			✓
Category ratings	CAT II 1000V, CAT III 600V		

Features

Manual range/True RMS	NCV/hFE/Max/Min
Data hold/REL	Diode test/Continuity test
Audible/visual alarm (NCV/continuity)	High voltage false detection: 1000Vrms
Current (AC/DC) mode memory	Over-current alarm: ≥20A
Low battery indication: ≤2.5V	Auto power off/LCD Backlight
Fuse blowing alarm (mA only): Input overload or misoperation	



Fuse blowing alarm (mA only)

Characteristics

Standard accessories	Batteries, test lead, k-type temperature probe (UT890C), English manual
Power	1.5V battery (R03) x 2
Display	60 x 35mm
Product size	183 x 88 x 56mm
Product net weight	346g
Standard individual packing	Gift box
Standard quantity per carton	40pcs
Standard carton measurement	645 x 450 x 340mm
Standard carton gross weight	23.3kg